

## SCM100ASL PRO



25mm/1" 'Dual suspension' głośnik wysokotonowy ATC 'S-spec'

12"/314mm głośnik basowy 'SL' spec

Głośnik średniotonowy 75mm ATC "Super Dome"

Wbudowany wzmacniacz Tri-amp 350W

LF EQ- korektor dolnego pasma

Wskaźnik przesterowania

Gwarancja 6 lat



**Cena:** \$0,00

**Kategorie:** [Audio](#), [Monitory studyjne](#)



## GALLERY IMAGES



## OPIS

### Specification

Drivers: HF 1"/25mm, Mid 3"/75mm, LF 12"/314mm  
Amplitude Linearity ( $\pm 2$ dB): 65Hz-17kHz  
Cut-off Frequencies (-6dB, free-standing): 32Hz, 22kHz  
Horizontal Dispersion:  $\pm 80^\circ$ , Coherent

Vertical Dispersion:  $\pm 10^\circ$ , Coherent  
Max. Continuous SPL (1 metre): 115dB  
Crossover Frequencies: 380Hz, 3.5kHz  
Input Connectors: Male XLR  
Input Sensitivity: 1V  
Input Sensitivity Trim: 0dB to -6dB/1V – 2V (continuously variable via rear panel trimmer)  
Input Impedance: Balanced > 10k $\Omega$   
Amplifier Output: Bass 200W, Mid 100W, High 50W  
Filters: Even Order Critically Damped  
Overload Protection: Active FET momentary gain reduction plus thermal tweeter protection  
Front Panel Indicators: Power On indicator, Gain Reduction warning  
LF EQ: 0dB to +6dB @ 40Hz (continuously variable via rear panel trimmer)  
Dimensions (HxWxD): 832 x 398 x 581mm (32.8" x 15.7" x 22.9") Depth with amplifier at rear adds 3"  
Weight: 65kg / 143lbs