

SCM150ASL PRO



25mm/1" 'Dual suspension' głośnik wysokotonowy ATC 'S-spec'

15"/375mm głośnik basowy 'SL' spec

Głośnik średniotonowy 75mm ATC "Super Dome"

Wbudowany wzmacniacz Tri-amp 350W

LF EQ- korektor dolnego pasma

Wskaźnik przesterowania

Gwarancja 6 lat



Cena: \$0,00

Kategorie: [Audio](#), [Monitory studyjne](#)



GALLERY IMAGES



OPIS

Specification

Drivers: HF 1"/25mm, Mid 3"/75mm, LF 15"/375mm
Amplitude Linearity (± 2 dB): 60Hz-17kHz
Cut-off Frequencies (-6dB, free-standing): 25Hz, 22kHz
Horizontal Dispersion: $\pm 80^\circ$, Coherent

Vertical Dispersion: $\pm 10^\circ$, Coherent
Max. Continuous SPL (1 metre): 117dB
Crossover Frequencies: 380Hz, 3.5kHz
Input Connectors: Male XLR
Input Sensitivity: 1V
Input Sensitivity Trim: 0dB to -6dB/1V – 2V (continuously variable via rear panel trimmer)
Input Impedance: Balanced > 10k Ω
Amplifier Output: Bass 200W, Mid 100W, High 50W
Filters: Even Order Critically Damped
Overload Protection: Active FET momentary gain reduction plus thermal tweeter protection
Front Panel Indicators: Power On indicator, Gain Reduction warning
LF EQ: 0dB to +6dB @ 40Hz (continuously variable via rear panel trimmer)
Dimensions (HxWxD): 884 x 498 x 568mm (34.8" x 19.6" x 25.5") Depth with amplifier at rear adds 3"
Weight: 75kg / 165lbs