

SCM200ASL PRO



Główny monitor dużego formatu

34mm głośnik wysokotonowy o miękkiej kopułce

2 głośniki basowe 12"/314mm "SL" spec

Głośnik średniotonowy 75mm ATC "Super Dome"

Wzmacniacz P4 zamontowany w obudowie rack 850W w klasie A/B

Gwarancja 6 lat.



Cena: \$0,00

Kategorie: [Audio](#), [Monitory studyjne](#)



GALLERY IMAGES



OPIS

Specification

Drivers: HF 1.25"/34mm, Mid 3"/75mm, LF 2 x 12"/314mm

Amplitude Linearity (± 2 dB): 60Hz-12kHz

Cut-off Frequencies (-6dB, free-standing): 32Hz, 20kHz (free standing) 25Hz, 20kHz (soffit mounted)

Horizontal Dispersion: $\pm 80^\circ$, Coherent

Vertical Dispersion: $\pm 10^\circ$, Coherent

Max. Continuous SPL (1 metre): 118dB

Crossover Frequencies: 380Hz, 3.5kHz

Input Connectors: Male XLR

Input Sensitivity: 2V

Input Impedance: Balanced $> 10k\Omega$

Amplifier Output: Bass 275+275W, Mid 200W, High 100W

Filters: Even Order Critically Damped

Overload Protection: Active FET momentary gain reduction plus thermal tweeter protection

Front Panel Indicators: N/A

LF EQ: N/A

Dimensions (HxWxD): 830 x 730 x 440mm (32.7" x 28.7" x 17.3")

Weight: 116kg / 255.2lbs