

SCM300ASL PRO



Główny monitor dużego formatu

34mm głośnik wysokotonowy o miękkiej kopułce

2 głośniki basowe 15"/375mm "SL" spec

Głośnik średniotonowy 75mm ATC "Super Dome"

Wzmacniacz P4 zamontowany w obudowie rack 850W w klasie A/B

Gwarancja 6 lat




Cena: \$0,00

Kategorie: [Audio](#), [Monitory studyjne](#)



GALLERY IMAGES



OPIS

Specification

Drivers: HF 1.25"/34mm, Mid 3"/75mm, LF 2 x 15"/375mm
Amplitude Linearity (± 2 dB): 50Hz-12kHz
Cut-off Frequencies (-6dB): 25Hz, 20kHz (free standing) 20Hz, 20kHz (soffit mounted)
Horizontal Dispersion: $\pm 80^\circ$, Coherent
Vertical Dispersion: $\pm 10^\circ$, Coherent
Max. Continuous SPL (1 metre): 121dB
Crossover Frequencies: 380Hz, 3.5kHz
Input Connectors: Male XLR
Input Sensitivity: 2V
Input Impedance: Balanced $> 10k\Omega$
Amplifier Output: Bass 275+275W, Mid 200W, High 100W
Filters: Even Order Critically Damped
Overload Protection: Active FET momentary gain reduction plus thermal tweeter protection
Front Panel Indicators: N/A
Dimensions (HxWxD): 884 x 925 x 460mm (34.8" x 36.4" x 18.7")
Weight: 140kg / 308lbs