

ATEM 1 M/E ADVANCED PANEL



The new ATEM 1 M/E Advanced Panel is an elegantly designed professional hardware control panel for all ATEM switchers. It combines modern design with the latest broadcast technology for faster workflows. The new design features a built in LCD and high quality curved buttons that help reduce incorrect key presses. The buttons also have color backlighting to help you quickly recognize important keys. You also get a professional joystick for DVE and camera adjustments, smooth weighted t-bar fader and much more. The buttons feature dynamic displays that allow full customization of the labels as well as custom colors. The shift buttons allow you to double up the number of inputs by selecting a second set of shifted source buttons so you can control up to 20 inputs. The compact size and durable design of the ATEM 1 M/E Advanced Panel fits in a standard equipment rack, making it perfect for shelf mounting in broadcast trucks, mobile racks and fly away kits.

Cena:

Kategorie: [Video](#), [Produkcja](#), [Miksery wizyjne](#), [Broadcast](#), [Miksery wizyjne](#)



OPIS

Connections

Ethernet

2 x 10/100/1000 BaseT with loop output for additional control panels or computers

Software Updates

1 x USB-C for firmware updates

Product Specifics

Direct Cross Points

10

Shifted Cross Points

20

Crosspoint Button Type

Tri-Color LED

Crosspoint Label

3 rows 24 character LCD

Next Transition Selectors

BKG, Key 1 - Key 4.

On-Air indicator

4

Power Status Indicators

None

DSK Transition Selectors

Auto, Cut, Tie/Preview.

Preview Transition

1

Transition Rate Displays

Via main menu

LCD Menu Displays

3



Menu Control

20 buttons

Dedicated Macro Buttons

10

Multi Control Buttons

None

Destination Bus

1

Source Select Bus

1

Fader Bar

1

3 Axis Joystick

1

Numeric Keypad

1

Software

Software Applications

ATEM Software Control Panel.

Operating Systems

Mac 10.14 Mojave,
Mac 10.15 Catalina or later.
Windows 8.1 and 10.

Power Requirements

Input Voltage

1 x Internal 100 - 240V AC.

Redundant Power

Yes

Power Usage

45W

Physical Specifications

Environmental Specifications

Operating Temperature

0° to 40° C (32° to 104° F)

Storage Temperature

-20° to 60° C (-4° to 140° F)

Relative Humidity

Up to 95%



What's Included

ATEM 1 M/E Advanced Panel

Warranty

12 Month Limited Manufacturer's Warranty.