

## ATEM 2 M/E ADVANCED PANEL



The 2 M/E model features 2 M/E rows with 20 input buttons and 2 independent system control LCDs for each row. Plus each row can control up to 4 M/Es in larger switchers. Both rows and all input buttons include LCDs for custom labeling. Each row also includes an independent select bus!



**Cena:**

**Kategorie:** [Video](#), [Produkcja](#), [Miksery wizyjne](#), [Broadcast](#), [Miksery wizyjne](#)

**OPIS**

## **Connections**

### **Ethernet**

4 x 10/100/1000 BaseT with loop output for additional control panels or computers.

### **Software Updates**

1 x USB-C for firmware updates.

## **Product Specifics**

### **Number of Mix Effects Rows**

2

### **Direct Cross Points**

20

### **Shifted Cross Points**

40

### **Crosspoint Button Type**

Tri-Color LED

### **Crosspoint Label**

6 rows 24 character LCD

### **Next Transition Selectors**

2 x BKG, Key 1 - Key 4.

**On-Air indicator**

8

**Power Status Indicators**

None

**DSK Transition Selectors**

Auto, Cut, Tie/Preview x 2

**Preview Transition**

2

**Transition Rate Displays**

Via main menu

**LCD Menu Displays**

2

**Menu Control**

20 buttons x 2

**Dedicated Macro Buttons**

2 x 20

**Transport Control Buttons**

8

## **Destination Bus**

2

## **Source Select Bus**

2

## **Fader Bar**

2

## **3 Axis Joystick**

1

## **Numeric Keypad**

1

## **Software**

### **Software Applications**

ATEM Software Control Panel.

### **Operating Systems**

Mac 10.14 Mojave,  
Mac 10.15 Catalina or later.  
Windows 10, 64-bit.

### **Power Requirements**

#### **Input Voltage**

2 x Internal 100 - 240V AC.

## **Redundant Power**

Yes

## **Power Usage**

150W

## **Physical Specifications**

### **Environmental Specifications**

#### **Operating Temperature**

0° to 40° C (32° to 104° F)

#### **Storage Temperature**

-20° to 60° C (-4° to 140° F)

#### **Relative Humidity**

Up to 95%

## **What's Included**

ATEM 2 M/E Advanced Panel

## **Warranty**

12 Month Limited Manufacturer's Warranty.