

## HYPERDECK STUDIO MINI

Blackmagicdesign



HyperDeck Studio Mini is a portable broadcast quality deck that records ProRes onto commonly available SD cards. You get 6G-SDI for recording all formats up to 2160p30, dual SD card slots for non-stop recording, a built in LCD screen and familiar VTR style front panel controls, all in a design that can be used on a desktop or in 1/3 of a standard rack space! HyperDeck Studio Mini also features 720p and 1080p 4:4:4:4 file support with fill and key outputs so it can be used as a source to provide broadcast graphics to live production switchers for downstream keying over live video!



**Cena:**

**Kategorie:** [Video](#), [Produkcja](#), [Rejestratory Video](#), [Broadcast](#), [Rejestratory Video](#)

## GALLERY IMAGES



## OPIS

### Connections

#### SDI Video Inputs

1

#### SDI Video Outputs

2

#### SDI Rates

270Mb, 1.5G-SDI, 3G-SDI, 6G-SDI

#### HDMI Video Outputs

1 x HDMI type A connector.

#### Power over Ethernet

1 x Ethernet with Power over Ethernet

#### Analog Video Inputs

None.

**Analog Video Outputs**

None.

**Analog Audio Inputs**

None, embedded audio only.

**Analog Audio Outputs**

None, embedded audio only.

**Timecode connection**

None.

**SDI Audio Inputs**

16 channels embedded in SD and HD in QuickTime files.

**SDI Audio Outputs**

16 channels embedded in SD and HD in QuickTime files.

**HDMI Audio Inputs**

None.

**HDMI Audio Outputs**

8 channels embedded in SD, HD and UHD in QuickTime files.

**Reference Input**

Tri-Sync or Black Burst.

## Reference Generator

Tri-Sync or Black Burst.

## Computer Interface

1 x USB 2.0 type C for software updates and HyperDeck Utility software control.

Please [click here](#) for a summary of compatible media.

## Standards

### SD Video Standards

525i59.94 NTSC, 625i50 PAL

### HD Video Standards

720p50, 720p59.94, 720p60

1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60

1080PsF23.98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30

1080i50, 1080i59.94, 1080i60

### Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30

### SDI Compliance

SMPTE 259M, 292M, 296M and 425M

### SDI Metadata Support

HD RP 188 and closed captioning.

## **Audio Sampling**

Television standard sample rate of 48kHz and 24-bit.

## **Video Sampling**

4:4:4:4

## **Color Precision**

10-bit

## **Color Space**

REC 601, REC 709

## **Media**

### **Media**

2 x SD for SD, HD and Ultra recording.

### **Media Type**

UHS II and able to support ProRes 4444 playback and 422 recording.

### **Media Format**

Can format discs to ExFAT (Windows/Mac) or OS X Extended (Mac) file systems.

## **Supported Codecs**

DNxHD 220x, DNxHD 145, DNxHD 45, DNxHD 220x MXF, DNxHD 145 MXF, DNxHD 45 MXF, DNxHR HQX, DNxHR SQ, DNxHR LB, DNxHR HQX MXF, DNxHR SQ MXF, DNxHR LB MXF. ProRes 422 HQ QuickTime, ProRes 422 QuickTime, ProRes 422 LT QuickTime, ProRes 422 Proxy QuickTime. ProRes 4444 QuickTime in HD for fill and key playback, H.264 in 720p and 1080p.

## **Computer Capture**

None

## **FTP Clients**

Cyberduck, Transmit, FileZilla

## **Control**

### **Built-in Control Panel**

8 buttons for menu control, 2.2 inch color display, and a rotary wheel.

### **External Control**

RS-422 deck control, SDI start/stop, timecode run. Includes Blackmagic HyperDeck SDK and Ethernet HyperDeck Control Protocol. Supports remote FTP file upload.

## **Software**

### **Software Included**

Media Express, Disk Speed Test, Blackmagic System Preferences and Blackmagic driver (Mac only).

### **Internal Software Upgrade**

Firmware built into software driver. Loaded at system start, or via updater software.

## **Display**

Built in LCD for video, audio and timecode monitoring and menu settings  
2 x LED indicator lights above the SD slots.

## **Physical Installation**

1/3 rack unit size. Less than 7 inches deep.

## **Operating Systems**

Mac 10.14 Mojave,  
Mac 10.15 Catalina or later.  
Windows 8.1 and 10.

## **Power Requirements**

### **Power Supply**

1x Internal 100 - 240V AC.

## **Physical Specifications**

## **Environmental Specifications**

### **Operating Temperature**

0° to 40° C (0° to 104° F)

### **Storage Temperature**

-20° to 45° C (-4° to 113° F)

### **Relative Humidity**

0% to 90% non-condensing

## **What's Included**

HyperDeck Studio Mini  
SD card with software and user manual.

## **Warranty**

12 Month Limited Manufacturer's Warranty.