ONTHEAIR SWITCH

×

OnTheAir Switch can control many matrix video switchers through RS232. The application is AppleScriptable allowing it to be controlled from any application (even applications from third parties) using a simple USB to RS232 converter. It can be used as a standalone application or integrated with OnTheAir Video, MovieRecorder or OnTheAir Node.

0 0	OnTheAir Switch	1							
Connected: 样	Refresh	1	2	3	4	5	6	7	8
VTR1	VTR1	•	0	0	0	0	0	0	0
VTR2	Main Input	0	0	•	0	0	0	0	0
Main Output	VTR2	0	•	0	0	0	0	0	0
Output 4	Input 5	0	0	0	0	•	0	0	0
Output 5	Input 8	0	0	0	0	0	0	0	•
Output 6	Input 6	0	0	0	0	0	•	0	0
Output 7	Main Input	0	0	۰	0	0	0	0	0
Output 8	VTR2	0	•	0	0	0	0	0	0

Cena: Kategorie: <u>Broadcast</u>, <u>Automatyka emisji</u>

OPIS

We can theoratically support any Matrix Video Switcher, but we need to implement the protocol for it of course. Before buying OnTheAir Switch, you can check the specifications page to check which Matrix Video Switcher is already supported and if yours is not in the list, simply contact us to ask if your Switcher can be supported and how to proceed.