

## SMART VIDEOHUB 12G 40X40




Advanced 12G-SDI video router supports any SD, HD or Ultra HD SDI format on the same router at the same time. Smart Videohub 12G 40x40 features 40 inputs and 40 outputs and includes video reference, redundant power connections and an elegant machined metal front panel with large full HD LCD for monitoring and routing label display. Routing can be performed by direct button selection and the spin knob controller. 12G-SDI technology supports all SDI video standards up to 2160p60.


**Cena:**

**Kategorie:** [Video](#), [Produkcja](#), [Monitoring TV](#)





## GALLERY IMAGES



## OPIS

### Connections

#### SDI Video Inputs

40 x 10-bit SD-SDI, HD-SDI and 12G-SDI.

#### SDI Video Outputs

40 x 10-bit SD-SDI, HD-SDI and 12G-SDI.

## **SDI Rates**

DVB-ASI, 270Mb, 1.5G, 3G, 6G, 12G.

## **Video Input Re-Sync**

None.

## **SDI Reclocking**

On all SDI outputs.

## **Reference Inputs**

Tri-Sync or Black Burst.

## **Reference Outputs**

Reference terminating loop output.

## **Control Panel Connection**

Ethernet.

## **Serial Control Connection**

DB-9 RS-422.

## **Multi Rate Support**

Auto detection of SD, HD or 6G-SDI. Simultaneous routing of 4K, HD, SD video and DVB-ASI.

## **Updates**

USB

## Front Panel Router Control

40 buttons for local control of Videohub. 6 buttons and scroll wheel for control of LCD display or RJ45 Ethernet. RS-422.

## Router Configuration

Via front panel LCD or RJ45 Ethernet.

## RS-422 Router Control

1 x input for controlling router crosspoint switching.

## Standards

### SD Video Standards

525i59.94 NTSC, 625i50 PAL

### HD Video Standards

720p50, 720p59.94, 720p60  
1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p47.95, 1080p48, 1080p50,  
1080p59.94, 1080p60  
1080PsF23,98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30  
1080i50, 1080i59.94, 1080i60

### 2K Video Standards

2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI, 2Kp29.97 DCI, 2Kp30 DCI, 2Kp47.95 DCI, 2Kp48 DCI,  
2Kp50 DCI, 2Kp59.94 DCI, 2Kp60 DCI  
2KPsF23.98 DCI, 2KPsF24 DCI, 2KPsF25 DCI, 2KPsF29.97 DCI, 2KPsF30 DCI

### Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30, 2160p47.95, 2160p48, 2160p50,  
2160p59.94, 2160p60

## **4K Video Standards**

4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI, 4Kp29.97 DCI, 4Kp30 DCI, 4Kp47.95 DCI, 4Kp48 DCI, 4Kp50 DCI, 4Kp59.94 DCI, 4Kp60 DCI

## **SDI Compliance**

SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE 424M, SMPTE 425M  
Level A and B

SMPTE 2081-1, SMPTE 2081-10, SMPTE 2082-10, ITU-R BT.656 and ITU-R BT.601

## **SDI Video Sampling**

4:2:2 and 4:4:4

## **SDI Audio Sampling**

Television standard sample rate of 48kHz and 24-bit.

## **SDI Color Precision**

10-bit 4:2:2 and 4:4:4

## **SDI Color Space**

YUV or RGB

## **SDI Auto Switching**

Automatically selects between SD-SDI, HD-SDI, 12G-SDI and DVB-ASI on each input so that each input can be running a different television standard.

## **SDI Metadata Support**

Video payload identification ancillary data as per SMPTE 352M.

## **Control**

### **Built in Control Panel**

40 buttons for local control of Videohub with 6 buttons and scroll wheel for menu control. 5 inch color display.

### **External Control Panel**

Includes Blackmagic Videohub software control panel for Mac and Windows. Supports Blackmagic Smart Control and Blackmagic Master Control hardware panels. Includes Blackmagic Videohub SDK and Ethernet Videohub Control Protocol.

## **Software**

### **Software Control**

Router control included free for Windows™ and Mac™.

### **Internal Software Upgrade**

Via included updater application.

## **Operating Systems**

Mac 10.14 Mojave,  
Mac 10.15 Catalina or later.  
Windows 8.1 and 10.

## **Display**

### **Displays**

Built in 5 inch LCD for video and menu settings.

## Power Requirements

### Power Supply

2 x Internal 90 - 240V AC. IEC power cables required.

### Power Fail Protection

Crosspoint connections preserved and restored instantly at power on.

## Physical Specifications

### Physical Installation

2 rack unit size. Less than 6 inches deep.

## Environmental Specifications

### Operating Temperature:

0° to 40° C (32° to 104° F)

### Storage Temperature:

-20° to 45° C (-4° to 113° F)

### Relative Humidity:

0% to 90% non-condensing

## What's Included

Smart Videohub 12G 40x40

SD card with software and manual

## Warranty

3 Year Limited Manufacturer's Warranty, and 12 Month Warranty on the front panel.