SCM100ASL PRO

25mm/1’’ ‘Dual suspension’ głośnik wysokotonowy ATC ‘S-spec’
12”/314mm głośnik basowy ‘SL’ spec
Głośnik średniotonowy 75mm ATC ‘’Super Dome’’
Wbudowany wzmacniacz Tri-amp 350W
LF EQ- korektor dolnego pasma
Wskaźnik przesterowania
Gwarancja 6 lat



Cena: $0,00
Kategorie: Audio, Monitory studyjne



GALLERY IMAGES







OPIS

Specification

Drivers: HF 1″/25mm, Mid 3″/75mm, LF 12″/314mm
Amplitude Linearity (±2dB): 65Hz-17kHz
Cut-off Frequencies (-6dB, free-standing): 32Hz, 22kHz
Horizontal Dispersion: ±80°, Coherent

Vertical Dispersion: ±10°, Coherent
Max. Continuous SPL (1 metre): 115dB
Crossover Frequencies: 380Hz, 3.5kHz
Input Connectors: Male XLR
Input Sensitivity: 1V
Input Sensitivity Trim: 0dB to -6dB/1V – 2V (continuously variable via rear panel trimmer)
Input Impedance: Balanced > 10kΩ
Amplifier Output: Bass 200W, Mid 100W, High 50W
Filters: Even Order Critically Damped
Overload Protection: Active FET momentary gain reduction plus thermal tweeter protection
Front Panel Indicators: Power On indicator, Gain Reduction warning
LF EQ: 0dB to+6dB @ 40Hz (continuously variable via rear panel trimmer)
Dimensions (HxWxD): 832 x 398 x 581mm (32.8″ x 15.7″ x 22.9″) Depth with amplifier at rear adds 3″
Weight: 65kg / 143lbs