SCM300ASL PRO

Główny monitor dużego formatu
34mm głośnik wysokotonowy o miękkiej kopułce
2 głośniki basowe 15’’/375mm ‘’SL’’ spec
Głośnik średniotonowy 75mm ATC ‘’Super Dome’’
Wzmacniacz P4 zamontowany w obudowie rack 850W w klasie A/B
Gwarancja 6 lat





Cena: $0,00
Kategorie: Audio, Monitory studyjne

GALLERY IMAGES



OPIS

Specification

Drivers: HF 1.25″/34mm, Mid 3″/75mm, LF 2 x 15″/375mm
Amplitude Linearity (±2dB): 50Hz-12kHz
Cut-off Frequencies (-6dB): 25Hz, 20kHz (free standing) 20Hz, 20kHz (soffit mounted)
Horizontal Dispersion: ±80°, Coherent
Vertical Dispersion: ±10°, Coherent
Max. Continuous SPL (1 metre): 121dB
Crossover Frequencies: 380Hz, 3.5kHz
Input Connectors: Male XLR
Input Sensitivity: 2V
Input Impedance: Balanced > 10kΩ
Amplifier Output: Bass 275+275W, Mid 200W, High 100W
Filters: Even Order Critically Damped
Overload Protection: Active FET momentary gain reduction plus thermal tweeter protection
Front Panel Indicators: N/A
Dimensions (HxWxD): 884 x 925 x 460mm (34.8″ x 36.4″ x 18.7″)
Weight: 140kg / 308lbs